




Perfecta SECURITY RIM LOCK







PRODUCT:

Featuring generously sized deadbolts and multiple latch points, the Perfecta rim lock - available as the 911, 913 and 915 series - may be used to increase the level of security of main entrance doors in wood.

OPERATING:

Latch retracted from external side with key and from internal side with key or pull bolt. Deadbolt operated from external side with key and from internal side with key or knob.

RANGE:

- Locks with 1 latching point (lateral)
- Locks with 3 latching points (three-point)
- Locks with 5 latching points (five-point)
- Locks with deadbolt only (5 pistons) or with latch and deadbolt (4 pistons + one latch at bottom)
- Locks with internal side key or internal side knob

STANDARDS:

Latch and deadbolt model with 3 latching points, with A2P* certification (1 star)

Latch and deadbolt model with 5 latching points, with A2P* certification (1 star)

TEXT FOR SPECIFICATIONS:

Iseo Perfecta series 911-913-915 security rim locks with from one lateral latching point to up to 5 latching points with arms and a supplementary deviator. Overall central lock dimensions H $160 \times 130 \, \text{mm}$, with key aperture 61 mm from edge of lock.

MATCHING ACCESSORIES:

- Arm kit for three latching point configuration
- Arm and deviator kit for five latching point configuration
- Optional accessories for applications with special requisites such as to angle pieces to route arms around obstacles, adjustable brackets to create an upper latching point in accordance with existing overlaps, floor bushes for the lower latching point and flat or recessed guide escutcheons to cater for different thicknesses of door.



TECHNICAL FEATURES

Works with plunger lock key.

Case size 61 mm.

Right or left handed.

External plunger cylinder, diam. 27 x 52 mm (60 mm available as option).

3 plunger lock keys included, blank key for duplicates art. 990001.

Vertical arm travel 21 mm.

In dark bronze paint finish.

HIGHLIGHTS

- Increase the security of an existing door with a multiple latching point rim lock.
- Lock certified in accordance with French A2P* standard (1 star).
- Deadbolt with four 18 mm diameter pistons, with 40 mm excursion (4 turns).
- Latch measuring 18 mm in diameter with 15 mm protrusion.
- Telescoping arms with 18 mm diameter ferrule for doors up to 2,660 mm in height.
- 33 mm diameter security escutcheon to protect outer cylinder.